

**TECHNICAL DATA SHEET****PRODUCT DESCRIPTION**

A low density, solvent-free epoxy fairing filler for marine and industrial applications. Designed to provide optimum handling and machining characteristics. Forms a strong permanent waterproof compound that is easy to sand.

**For use on**

Filling and fairing work on large surface areas to smoothen and remove imperfections. The product's low specific weight (0.7kg/ litre) and long pot-life (400ml: 20-30 minutes) makes it ideal for use extensively without adding much weight on the substrate.

**DIRECTIONS FOR USE****Usage**

The resin and hardener must be thoroughly mixed together into a uniform colour. Care should be taken to avoid excessive air entrapment. The use of a flat board for mixing on is recommended as this makes mixing easier and enables larger batch to be mixed at one time.

Product designed for application by spatula, putty knife or trowel.

**Coverage**

N/A

**Mixing Ratio**

1 to 1 by volume

**Recoating time**

N/A

**Thinner**

N/A

**Curing Time**

6 to 8 hrs

**Pack Sizes**

N/A

**PRODUCT INFORMATION**

**Aged Recoat** : Sand Surface  
**Finish** :Light Blue

**QUICK TIPS****Health and Safety**

Provide adequate ventilation during use. Avoid contact with skin and eyes. Avoid breathing dust vapour or spray. Wear eye protection and gloves during use.

**RECOMMENDED SPRAY GUN SETUP: N/A**

N/A

**CONTACT US  
TODAY  
FOR PAINT ESTIMATES  
AND TECHNICAL ADVICE**

**OMI Coatings**

102F Pasir Panjang Road #01-01  
Citilink Warehouse Complex  
Singapore 118530



**T. +65 6777 6001**  
**F. +65 6777 9006**



**omicoat.com**  
**info@omicoat.com**