



**TECHNICAL DATA SHEET**

**PRODUCT DESCRIPTION**

A low density, solvent-free epoxy fairing filler for marine and industrial applications. Designed to provide optimum handling and machining characteristics. Forms a strong permanent waterproof compound that is easy to sand.

**DIRECTIONS FOR USE**

**Usage**

All marine and industrial applications for filling, repair and fairing work.. Forms a strong, permanent water proof filler that is easy to sand and will bond to a variety of substrates.

**Coverage**

Depending on usage & substrate

**Mixing Ratio**

2:1 by volume.

**Recoating time**

4 hours

Sand surface if time exceeds or when preparing for overcoating with a paint system.

**Thinner**

N/A

**Curing Time**

8-10 hours

**Pack Sizes**

875GM, 1.75KG, 7KG

**QUICK TIPS**

Product designed for spatula, putty knife or trowel

Key to ensuring a good job is to Ensure proper surface preparation on various substrates before coating.

Use T500 thinner if necessary to degrease or wipe down surface prior to product application

**RECOMMENDED SYSTEM**

Universal Primer (Anticorrosion)  
Everguard Epoxy Undercoat  
Everguard Hi Build Primer  
Suitable OM Topcoat

**CONTACT US  
TODAY  
FOR PAINT ESTIMATES  
AND TECHNICAL ADVICE**

