



## TECHNICAL DATA SHEET

### PRODUCT DESCRIPTION

A non-shrinking, high strength gap filling two pack epoxy resin glue. It can be used for bonding a wide range of materials such as wood, fibreglass ceramics, plastics and metals. Provides a strong waterproof joint

### PRODUCT INFORMATION

**Colour** :Light Amber

### DIRECTIONS FOR USE

#### Usage

All marine and industrial applications where a high performance epoxy resin-based adhesive is required. Offers non staining glue line when cured.

#### Coverage

Depending on usage & substrate

#### Mixing Ratio

2:1 by volume.

#### Clamping time

24 hours  
Sand surface if time exceeds or when preparing for overcoating with a paint system

#### Thinner

N/A

#### Curing Time

24 Hours

#### Pack Sizes

500GM, 1KG, 6.3KG

### QUICK TIPS

Product designed for spatula, putty knife or trowel

Key to ensuring a good job is to  
Ensure proper surface preparation  
on various substrates before coating.

Use T500 thinner if necessary to degrease or wipe  
down surface prior to product application

### RECOMMENDED SYSTEM

Universal Primer (Anticorrosion)  
Everguard Epoxy Undercoat  
Everguard Hi Build Primer  
Suitable OM Topcoat

**CONTACT US  
TODAY  
FOR PAINT ESTIMATES  
AND TECHNICAL ADVICE**

