



TECHNICAL DATA SHEET

PRODUCT DESCRIPTION

Surfacing undercoat with water resistance properties for above waterline applications. High opacity and good film build effectively hide substrate and level up minor surface imperfection.

DIRECTIONS FOR USE

Usage

Boat hulls after fairing, steel and aluminium after priming, or directly on fibreglass and timber. Provides excellent base for OceanMaster Marine Gloss and other similar coatings.

Coverage

11 sq.m / L

Mixing Ratio

N/A

Recoating time

2-3 hours

Thinner

T100

Curing Time

6 hours

Pack Sizes

5 litres

PRODUCT INFORMATION

Wet Film Thickness : 90 microns

Dry Film Thickness : 42 microns

Aged Recoat : Sand surface

Finish : Off White

QUICK TIPS

Health and Safety

Provide adequate ventilation during use. Avoid contact with skin and eyes. Avoid breathing dust vapour or spray. Wear eye protection and gloves during use.

RECOMMENDED SPRAY GUN SETUP: BINKS

N/A

**CONTACT US
TODAY
FOR PAINT ESTIMATES
AND TECHNICAL ADVICE**



OMI Coatings

102F Pasir Panjang Road #01-01
Citilink Warehouse Complex
Singapore 118530



T. +65 6777 6001
F. +65 6777 9006



omicoat.com
info@omicoat.com