



TECHNICAL DATA SHEET

PRODUCT DESCRIPTION

A single-pack coal tar pitch aluminium vinyl underwater primer designed for protection & maintenance underwater to repair existing coatings. An ideal as an anti-corrosive system prior to application of antifouling.

DIRECTIONS FOR USE

Usage

Above and below water on suitably prepared steel, wood and fibreglass substrates. Product designed for application by spray, roller or brush.

Coverage

4 - 5 sq.m / L

Mixing Ratio

N/A

Recoating time

8 hours

Thinner

T100

Curing Time

4 hours

Pack Sizes

5 litres

PRODUCT INFORMATION

Wet Film Thickness : 130 microns

Dry Film Thickness : 45 microns

Aged Recoat : Sand surface

Finish :Light Grey

QUICK TIPS

Health and Safety

Provide adequate ventilation during use. Avoid contact with skin and eyes. Avoid breathing dust vapour or spray. Wear eye protection and gloves during use.

RECOMMENDED SPRAY GUN SETUP: BINKS

N/A

**CONTACT US
TODAY
FOR PAINT ESTIMATES
AND TECHNICAL ADVICE**



OMI Coatings

102F Pasir Panjang Road #01-01
Citilink Warehouse Complex
Singapore 118530



T. +65 6777 6001
F. +65 6777 9006



omicoat.com
info@omicoat.com