

**TECHNICAL DATA SHEET****PRODUCT DESCRIPTION**

The newly formulated ultimate two-pack polyurethane high gloss clear finish designed for application where a tough, durable glossy finish is required.

**DIRECTIONS FOR USE****Usage**

As a high gloss clear topcoat over a polyurethane coloured finish coat. Suitable for direct application to all new exotic timbers or over an epoxy two component timber preservative materials.

**Coverage**

11 sqm/litre – depending on usage & substrate

**Mixing Ratio**

3:1 by volume.

**Recoating time**

4-6 hours max  
Sand surface if time exceeds or when preparing for overcoating with a paint system

**Thinner**

T300

**Curing Time**

48 hours, 07 days full cure

**Pack Sizes**

1 Litre / 4 litre

**QUICK TIPS**

Product designed for spray/ roller application

Key to ensuring a good job is to ensure proper surface preparation on various substrates before coating.

Use T500 thinner if necessary to degrease or wipe down surface prior to product application

Apply min 2 coats of Everguard undercoat before rolling on the Polygloss Clear. This is important for fibreglass / wooden decks where moisture might hinder proper adhesion of material. For metal surfaces, ensure 2 coats of Universal anticorrosive primer before undercoat.

**RECOMMENDED SPRAY GUN SETUP : BINKS**

FLUID NOZZLE: 63-BSS 45-6321 (1.2MM)

FLUID NEEDLE: 563A 47-56310

AIR NOZZLE 63-P 46-6000

Wet Film Thickness: 85 Microns

Dry Film Thickness: 40 Microns

**CONTACT US  
TODAY  
FOR PAINT ESTIMATES  
AND TECHNICAL ADVICE**

**OMI Coatings**

102F Pasir Panjang Road #01-01  
Citilink Warehouse Complex  
Singapore 118530



**T. +65 6777 6001**  
**F. +65 6777 9006**



**omicoat.com**  
**info@omicoat.com**